### The

# CORTADO MKIII CONTACT MICROPHONE

# ZEPPELIN DESIGN LABS

The Cortado MkIII is a high quality contact microphone containing a robust, sensitive transducer designed for use in professional applications. The internal class-A pre-amplifier is fully balanced with a low impedance output, which allows for wide bandwidth, low signal losses, and high signal to noise ratio. The Cortado contact microphone is now in it's third incarnation; with improvements to make it more robust, extra versatile, and easier to use. The Mark III offers an extremely robust, yet sensitive transducer connected to the pre-amp chassis via a high quality 6 foot long cable. User-controlled features such as a -10dB pad and "bass boost" (high pass filter) have been added, making the Mark III extremely versatile in any application.


- Built in preamp circuit capable of driving a balanced signal through hundreds of feet of cable.
- Preamp circuit features hand-matched, high quality components for a low noise floor and tonal transparency.
- Bandwidth: 23Hz 40kHz
- Fully balanced signal path for extremely low noise floor
- -10dB switchable pad to attenuate loud sound sources.
- Sensor is encased in an extremely robust metal enclosure for near-indestructibility.
- 6 foot (1.8m) high quality shielded cable from chassis to sensor.
- 20 gauge steel chassis.
- Requires phantom power from a standard XLR mic cable.







#### DIMENSIONS



#### TECHNICAL SPECIFICATIONS

Transducer type: PZT

Frequency response (see graph): 23Hz-40kHz, 150Hz-40kHz


Output impedance (at 1kHz): ~4.4k ohms
Built-in preamp gain: ~150 (without pad), ~50 (with pad)

Circuitry topology: Class-A preamp, fully balanced

Operation temperature: -40 to 80 degrees C

Operating phantom voltage: 24V - 48V

Phantom power current: ~1.3mA Sensor cable length: 6 ft. (1.8m)





## **ZEPPELIN DESIGN LABS**

2950 N. WESTERN
CHICAGO, IL
60618
www.zeppelindesignlabs.com

WWW.CORTADOMIC.COM